



# DEF DURA-METER™

- / Made of impact resistant Lexan™ faceplate
- / 100% moisture-sealed circuitry
- / Same great menu driven backlit display
- / Plumbed for both in-line and 90 degree applications
- / Includes a 2-year Warranty & Maintenance Program



**ORDERING INFORMATION**  
**DP-3000D**

SPECIFICATIONS	
Operating Temp	-10°F to 130°F, -23°C to 54°C
Flow Rate	2 to 22GPM, 4 to 44LPM
ISO22241-3 Compliant	Yes
Meter Accuracy	+ / - .5%
Maximum Pressure	40 PSI
Wetted Materials	Polypropylene; 304 Stainless Steel; Ryton; EPDM seals



# DEF DURA-PUMP™

- / Updated High-Flow pump with up to 18GPM/68LPM free flow rate (20% improvement over previous pump) and 13+GPM/49+LPM with ¾" discharge hose and nozzle
- / Self-priming diaphragm pump with internal bypass
- / Motor thermally protected from overheating
- / 30-minute duty cycle
- / Suction port has 2" Male NPT and 1" Female NPT
- / Pump is easily field serviceable
- / 10-minute auto-shut off motor (available in 110V only)
- / Includes a 2-year Warranty & Maintenance Program

**ORDERING INFORMATION**  
**DEF-6018E-12** 12 Volt    **DEF-6018E-110** 110 Volt

SPECIFICATIONS	
Check Valve	Internal; EPA 165.45 compliant
Vertical Suction Lift	Self-priming to 10ft, 3m
Power Cord	12 Volt: 20ft, 6m; 110 Volt: 6.5ft, 2m
Motor	1/4 HP, 186W
Amps	12 Volt: 18.5; 110 Volt: 2.0
Suction Port	2" Male and 1" Female NPT thread
Discharge Port	1" Female NPT thread
ISO22241-3 Compliant	Yes
Wetted Materials	Polypropylene; Santoprene; PVDF (Kynar®); 304 Stainless Steel; EPDM seals