

DURA-METER™

PRODUCT SPECIFICATIONS



Customer should always check calibration before use

Operating Temp	-10°F to 130°F
Flow Rate	2 to 22 GPM
Meter Accuracy	+/- .5%
Backlit LCD Display	Yes; with back-light timeout
Max Pressure	40 psi
Power Source	4 "AAA" batteries; strength indicator
Nutating Disc	Yes
Wetted Materials	Polypropylene; 304 Stainless Steel; Ryton; EPDM or Viton® Seals
Housing Chamber	Polypropylene
Moisture Sealed Construction	Yes; with sealed circuitry
Suction/ Discharge Ports	1" FNPT
Meter Reset Feature	Yes
Liquid Flash-point	100°F / 37.8° C
Total Fluid Count	Yes
Amount Metered	Yes
Batch Count	Yes
Units Measured	English or Metric; GPM or LPM
Control Panel	4 buttons
Chemically Resistant	Yes
Calibration Units	Gallons / Liters
Calibration	Quick List or Manual
Mounting Range	Fixed or In-line
Vibration / Shock Resistant	Yes
Info / Help Screen	Yes
Dimensions	5-1/4" W x 5-1/4" H x 4-1/4" D
Weight	1.5 lbs
EPA Compliant	Yes

- / Made of impact resistant Lexan™ faceplate
- / 100% moisture-sealed circuitry makes meter impervious to water intrusion
- / Menu driven backlit display
- / Plumbed both for in-line and 90 degree applications
- / Supported by a Quick List reference chart
- / Extended battery life with use of 4 "AAA" batteries
- / Faceplate over-molded with Santoprene and filled with gel for improved shock resistance
- / Includes 2 Year Service Warranty Plan

DP-3000E EPDM

DP-3000V Viton®

*Must specify EPDM (**product # and E**) or Viton® (**product # and V**) when ordering.*



DURA PRODUCTS

Technology with Lasting Value

www.DuraProducts.com

Arcadia, IN 46030 | 855-502-3872

©2015 Dura Products, Inc.