








TurboDrop® XL Medium Pressure

The TurboDrop® Venturi (TDXLV/TDVC) is the heart of the TurboDrop® XL nozzle. The Venturi (or injector) meters the flow and injects air into the spray fluid. The TurboDrop® Venturi utilizes a patented stabilization chamber and pulsation dampener which result in even mixing of air with the spray liquid, and a tighter more uniform droplet spectrum for a unique combination of drift control and coverage. The TurboDrop® Venturi is ISO color coded for flow rate. The pattern tip should be double the flow of the Venturi. For example, a blue 03 Venturi requires an 06 pattern tip.

The TurboDrop® XL nozzle is unique among air injection nozzles in that it was designed for contact chemicals, not just glyphosate (a systemic herbicide). In fact, the TurboDrop® XL, the TurboDrop® DualFan and the AirMix® are the only air injection nozzles recommended by Bayer CropScience for use with Liberty™ herbicide. The single fan XL can be used in most ag spray applications by choosing the appropriate combination of carrier rate and droplet size.

Pressure Range: 20-120 psi **Recommended Boom Height:** 18-36" (with 20" nozzle spacing)
Materials of Construction: Polyacetyl, EPDM, Ceramic (TDCXL/TACDF/TDVC)

	Liquid Pressure PSI	Droplet Size ASABE	Nozzle Capacity GPM	GALLONS PER ACRE BASED ON 20" NOZZLE SPACING															
				5 MPH	6 MPH	7 MPH	8 MPH	9 MPH	10 MPH	11 MPH	12 MPH	13 MPH	14 MPH	15 MPH	16 MPH	17 MPH	18 MPH	20 MPH	
	30	C	0.09	5.1	4.3	3.7	3.2	2.9	2.6	2.3	2.1	2.0	1.8	1.7	1.6	1.5	1.4	1.3	
	40	C	0.10	5.9	5.0	4.2	3.7	3.3	3.0	2.7	2.5	2.3	2.1	2.0	1.9	1.7	1.7	1.5	
	50	M	0.11	6.6	5.5	4.7	4.2	3.7	3.3	3.0	2.8	2.6	2.4	2.2	2.1	2.0	1.8	1.7	
	60	M	0.12	7.3	6.1	5.2	4.5	4.0	3.6	3.3	3.0	2.8	2.6	2.4	2.3	2.1	2.0	1.8	
	70	M	0.13	7.9	6.5	5.6	4.9	4.4	3.9	3.6	3.3	3.0	2.8	2.6	2.5	2.3	2.2	2.0	
	80	F	0.14	8.4	7.0	6.0	5.3	4.7	4.2	3.8	3.5	3.2	3.0	2.8	2.6	2.5	2.3	2.1	
	90	F	0.15	8.9	7.4	6.4	5.6	5.0	4.5	4.1	3.7	3.4	3.2	3.0	2.8	2.6	2.5	2.2	
	100	F	0.16	9.4	7.8	6.7	5.9	5.2	4.7	4.3	3.9	3.6	3.4	3.1	2.9	2.8	2.6	2.3	
120	F	0.17	10.3	8.6	7.3	6.4	5.7	5.1	4.7	4.3	4.0	3.7	3.4	3.2	3.0	2.9	2.6		
	30	C	0.13	7.7	6.4	5.5	4.8	4.3	3.9	3.5	3.2	3.0	2.8	2.6	2.4	2.3	2.1	1.9	
	40	C	0.15	8.9	7.4	6.4	5.6	5.0	4.5	4.1	3.7	3.4	3.2	3.0	2.8	2.6	2.5	2.2	
	50	M	0.17	10.0	8.3	7.1	6.2	5.5	5.0	4.5	4.2	3.8	3.6	3.3	3.1	2.9	2.8	2.5	
	60	M	0.18	10.9	9.1	7.8	6.8	6.1	5.5	5.0	4.5	4.2	3.9	3.6	3.4	3.2	3.0	2.7	
	70	M	0.20	11.8	9.8	8.4	7.4	6.5	5.9	5.4	4.9	4.5	4.2	3.9	3.7	3.5	3.3	2.9	
	80	M	0.21	12.6	10.5	9.0	7.9	7.0	6.3	5.7	5.3	4.8	4.5	4.2	3.9	3.7	3.5	3.2	
	90	F	0.23	13.4	11.1	9.5	8.4	7.4	6.7	6.1	5.6	5.1	4.8	4.5	4.2	3.9	3.7	3.3	
	100	F	0.24	14.1	11.7	10.1	8.8	7.8	7.0	6.4	5.9	5.4	5.0	4.7	4.4	4.1	3.9	3.5	
120	F	0.26	15.4	12.9	11.0	9.6	8.6	7.7	7.0	6.4	5.9	5.5	5.1	4.8	4.5	4.3	3.9		
	30	C	0.17	10.3	8.6	7.3	6.4	5.7	5.1	4.7	4.3	4.0	3.7	3.4	3.2	3.0	2.9	2.6	
	40	C	0.20	11.9	9.9	8.5	7.4	6.6	5.9	5.4	5.0	4.6	4.2	4.0	3.7	3.5	3.3	3.0	
	50	M	0.22	13.3	11.1	9.5	8.3	7.4	6.6	6.0	5.5	5.1	4.7	4.4	4.2	3.9	3.7	3.3	
	60	M	0.24	14.5	12.1	10.4	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.6	
	70	M	0.26	15.7	13.1	11.2	9.8	8.7	7.9	7.1	6.5	6.0	5.6	5.2	4.9	4.6	4.4	3.9	
	80	M	0.28	16.8	14.0	12.0	10.5	9.3	8.4	7.6	7.0	6.5	6.0	5.6	5.2	4.9	4.7	4.2	
	90	F	0.30	17.8	14.9	12.7	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.5	
	100	F	0.32	18.8	15.7	13.4	11.7	10.4	9.4	8.5	7.8	7.2	6.7	6.3	5.9	5.5	5.2	4.7	
120	F	0.35	20.6	17.1	14.7	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.1		
	30	VC	0.22	12.9	10.7	9.2	8.0	7.1	6.4	5.8	5.4	4.9	4.6	4.3	4.0	3.8	3.6	3.2	
	40	VC	0.25	14.9	12.4	10.6	9.3	8.3	7.4	6.8	6.2	5.7	5.3	5.0	4.6	4.4	4.1	3.7	
	50	C	0.28	16.6	13.8	11.9	10.4	9.2	8.3	7.5	6.9	6.4	5.9	5.5	5.2	4.9	4.6	4.2	
	60	M	0.31	18.2	15.2	13.0	11.4	10.1	9.1	8.3	7.6	7.0	6.5	6.1	5.7	5.3	5.1	4.5	
	70	M	0.33	19.6	16.4	14.0	12.3	10.9	9.8	8.9	8.2	7.6	7.0	6.5	6.1	5.8	5.5	4.9	
	80	M	0.35	21.0	17.5	15.0	13.1	11.7	10.5	9.5	8.8	8.1	7.5	7.0	6.6	6.2	5.8	5.3	
	90	M	0.38	22.3	18.6	15.9	13.9	12.4	11.1	10.1	9.3	8.6	8.0	7.4	7.0	6.6	6.2	5.6	
	100	M	0.40	23.5	19.6	16.8	14.7	13.0	11.7	10.7	9.8	9.0	8.4	7.8	7.3	6.9	6.5	5.9	
120	F	0.43	25.7	21.4	18.4	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.4		
	30	XC	0.26	15.4	12.9	11.0	9.6	8.6	7.7	7.0	6.4	5.9	5.5	5.1	4.8	4.5	4.3	3.9	
	40	VC	0.30	17.8	14.9	12.7	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.5	
	50	C	0.34	19.9	16.6	14.2	12.5	11.1	10.0	9.1	8.3	7.7	7.1	6.6	6.2	5.9	5.5	5.0	
	60	C	0.37	21.8	18.2	15.6	13.6	12.1	10.9	9.9	9.1	8.4	7.8	7.3	6.8	6.4	6.1	5.5	
	70	M	0.40	23.6	19.6	16.8	14.7	13.1	11.8	10.7	9.8	9.1	8.4	7.9	7.4	6.9	6.5	5.9	
	80	M	0.42	25.2	21.0	18.0	15.8	14.0	12.6	11.5	10.5	9.7	9.0	8.4	7.9	7.4	7.0	6.3	
	90	M	0.45	26.7	22.3	19.1	16.7	14.9	13.4	12.2	11.1	10.3	9.5	8.9	8.4	7.9	7.4	6.7	
	100	M	0.47	28.2	23.5	20.1	17.6	15.7	14.1	12.8	11.7	10.8	10.1	9.4	8.8	8.3	7.8	7.0	
120	M	0.52	30.9	25.7	22.0	19.3	17.1	15.4	14.0	12.9	11.9	11.0	10.3	9.6	9.1	8.6	7.7		
	30	XC	0.35	20.6	17.1	14.7	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.1	
	40	VC	0.40	23.8	19.8	17.0	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	5.9	
	50	C	0.45	26.6	22.1	19.0	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	6.6	
	60	C	0.49	29.1	24.2	20.8	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.3	
	70	M	0.53	31.4	26.2	22.5	19.6	17.5	15.7	14.3	13.1	12.1	11.2	10.5	9.8	9.2	8.7	7.9	
	80	M	0.57	33.6	28.0	24.0	21.0	18.7	16.8	15.3	14.0	12.9	12.0	11.2	10.5	9.9	9.3	8.4	
	90	M	0.60	35.6	29.7	25.5	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	8.9	
	100	M	0.63	37.6	31.3	26.8	23.5	20.9	18.8	17.1	15.7	14.4	13.4	12.5	11.7	11.0	10.4	9.4	
120	M	0.69	41.2	34.3	29.4	25.7	22.9	20.6	18.7	17.1	15.8	14.7	13.7	12.9	12.1	11.4	10.3		

	Liquid Pressure PSI	Droplet Size ASABE	Nozzle Capacity GPM	GALLONS PER ACRE BASED ON 20" NOZZLE SPACING															
				5 MPH	6 MPH	7 MPH	8 MPH	9 MPH	10 MPH	11 MPH	12 MPH	13 MPH	14 MPH	15 MPH	16 MPH	17 MPH	18 MPH	20 MPH	
 TDXL11005	30	XC	0.43	25.7	21.4	18.4	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.4	
	40	XC	0.50	29.7	24.8	21.2	18.6	16.5	14.9	13.5	12.4	11.4	10.6	9.9	9.3	8.7	8.3	7.4	
	50	VC	0.56	33.2	27.7	23.7	20.8	18.4	16.6	15.1	13.8	12.8	11.9	11.1	10.4	9.8	9.2	8.3	
	60	VC	0.61	36.4	30.3	26.0	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.1	
	70	C	0.66	39.3	32.7	28.1	24.6	21.8	19.6	17.9	16.4	15.1	14.0	13.1	12.3	11.6	10.9	9.8	
	80	C	0.71	42.0	35.0	30.0	26.3	23.3	21.0	19.1	17.5	16.2	15.0	14.0	13.1	12.4	11.7	10.5	
	90	M	0.75	44.6	37.1	31.8	27.8	24.8	22.3	20.3	18.6	17.1	15.9	14.9	13.9	13.1	12.4	11.1	
	100	M	0.79	47.0	39.1	33.5	29.3	26.1	23.5	21.3	19.6	18.1	16.8	15.7	14.7	13.8	13.0	11.7	
120	M	0.87	51.4	42.9	36.7	32.2	28.6	25.7	23.4	21.4	19.8	18.4	17.1	16.1	15.1	14.3	12.9		
 TDXL11006	30	XC	0.52	30.9	25.7	22.0	19.3	17.1	15.4	14.0	12.9	11.9	11.0	10.3	9.6	9.1	8.6	7.7	
	40	XC	0.60	35.6	29.7	25.5	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	8.9	
	50	XC	0.67	39.8	33.2	28.5	24.9	22.1	19.9	18.1	16.6	15.3	14.2	13.3	12.5	11.7	11.1	10.0	
	60	VC	0.73	43.6	36.4	31.2	27.3	24.2	21.8	19.8	18.2	16.8	15.6	14.5	13.6	12.8	12.1	10.9	
	70	VC	0.79	47.1	39.3	33.7	29.5	26.2	23.6	21.4	19.6	18.1	16.8	15.7	14.7	13.9	13.1	11.8	
	80	C	0.85	50.4	42.0	36.0	31.5	28.0	25.2	22.9	21.0	19.4	18.0	16.8	15.8	14.8	14.0	12.6	
	90	C	0.90	53.5	44.6	38.2	33.4	29.7	26.7	24.3	22.3	20.6	19.1	17.8	16.7	15.7	14.9	13.4	
	100	M	0.95	56.4	47.0	40.3	35.2	31.3	28.2	25.6	23.5	21.7	20.1	18.8	17.6	16.6	15.7	14.1	
120	M	1.04	61.7	51.4	44.1	38.6	34.3	30.9	28.1	25.7	23.7	22.0	20.6	19.3	18.2	17.1	15.4		
 TDXL11008	30	XC	0.69	41.2	34.3	29.4	25.7	22.9	20.6	18.7	17.1	15.8	14.7	13.7	12.9	12.1	11.4	10.3	
	40	XC	0.80	47.5	39.6	33.9	29.7	26.4	23.8	21.6	19.8	18.3	17.0	15.8	14.9	14.0	13.2	11.9	
	50	XC	0.89	53.1	44.3	37.9	33.2	29.5	26.6	24.1	22.1	20.4	19.0	17.7	16.6	15.6	14.8	13.3	
	60	XC	0.98	58.2	48.5	41.6	36.4	32.3	29.1	26.5	24.2	22.4	20.8	19.4	18.2	17.1	16.2	14.5	
	70	VC	1.06	62.9	52.4	44.9	39.3	34.9	31.4	28.6	26.2	24.2	22.5	21.0	19.6	18.5	17.5	15.7	
	80	VC	1.13	67.2	56.0	48.0	42.0	37.3	33.6	30.5	28.0	25.8	24.0	22.4	21.0	19.8	18.7	16.8	
	90	VC	1.20	71.3	59.4	50.9	44.6	39.6	35.6	32.4	29.7	27.4	25.5	23.8	22.3	21.0	19.8	17.8	
	100	C	1.26	75.1	62.6	53.7	47.0	41.7	37.6	34.2	31.3	28.9	26.8	25.0	23.5	22.1	20.9	18.8	
120	C	1.39	82.3	68.6	58.8	51.4	45.7	41.2	37.4	34.3	31.7	29.4	27.4	25.7	24.2	22.9	20.6		
 TDXL11010	30	XC	0.87	51.4	42.9	36.7	32.2	28.6	25.7	23.4	21.4	19.8	18.4	17.1	16.1	15.1	14.3	12.9	
	40	XC	1.00	59.4	49.5	42.4	37.1	33.0	29.7	27.0	24.8	22.8	21.2	19.8	18.6	17.5	16.5	14.9	
	50	XC	1.12	66.4	55.3	47.4	41.5	36.9	33.2	30.2	27.7	25.5	23.7	22.1	20.8	19.5	18.4	16.6	
	60	XC	1.22	72.7	60.6	52.0	45.5	40.4	36.4	33.1	30.3	28.0	26.0	24.2	22.7	21.4	20.2	18.2	
	70	XC	1.32	78.6	65.5	56.1	49.1	43.7	39.3	35.7	32.7	30.2	28.1	26.2	24.6	23.1	21.8	19.6	
	80	VC	1.41	84.0	70.0	60.0	52.5	46.7	42.0	38.2	35.0	32.3	30.0	28.0	26.3	24.7	23.3	21.0	
	90	VC	1.50	89.1	74.3	63.6	55.7	49.5	44.6	40.5	37.1	34.3	31.8	29.7	27.8	26.2	24.8	22.3	
	100	VC	1.58	93.9	78.3	67.1	58.7	52.2	47.0	42.7	39.1	36.1	33.5	31.3	29.3	27.6	26.1	23.5	
120	VC	1.73	102.9	85.7	73.5	64.3	57.2	51.4	46.8	42.9	39.6	36.7	34.3	32.2	30.3	28.6	25.7		
 TDXL11015 (uses 24 mesh)	30		1.30	77.2	64.3	55.1	48.2	42.9	38.6	35.1	32.2	29.7	27.6	25.7	24.1	22.7	21.4	19.3	
	40		1.50	89.1	74.3	63.6	55.7	49.5	44.6	40.5	37.1	34.3	31.8	29.7	27.8	26.2	24.8	22.3	
	50		1.68	99.6	83.0	71.2	62.3	55.3	49.8	45.3	41.5	38.3	35.6	33.2	31.1	29.3	27.7	24.9	
	60		1.84	109.1	90.9	77.9	68.2	60.6	54.6	49.6	45.5	42.0	39.0	36.4	34.1	32.1	30.3	27.3	
	70		1.98	117.9	98.2	84.2	73.7	65.5	58.9	53.6	49.1	45.3	42.1	39.3	36.8	34.7	32.7	29.5	
	80		2.12	126.0	105.0	90.0	78.8	70.0	63.0	57.3	52.5	48.5	45.0	42.0	39.4	37.1	35.0	31.5	
	90		2.25	133.7	111.4	95.5	83.5	74.3	66.8	60.8	55.7	51.4	47.7	44.6	41.8	39.3	37.1	33.4	
	100		2.37	140.9	117.4	100.6	88.0	78.3	70.4	64.0	58.7	54.2	50.3	47.0	44.0	41.4	39.1	35.2	
120		2.60	154.3	128.6	110.2	96.5	85.7	77.2	70.1	64.3	59.4	55.1	51.4	48.2	45.4	42.9	38.6		