



FLOWMETERS & SERVO VALVES



BUILT TOUGH, DESIGNED FOR ACCURACY

Turbine Flowmeters:

- Simple, Rugged, and Dependable
- Unique two-direction flow design - 2X working life

Magnetic Flowmeters:

- No moving parts
- Unaffected by fluid viscosity and density
- State-of-the-art accuracy

Servo Valves:

- Designed for responsive & precise control
- Fast acting & reliable

TURBINE FLOWMETERS

Our turbine flowmeters combine fast, accurate flow readings with rugged, dependable quality. Unique two-direction flow design — simply flip the flowmeter around to double its working life — flow measurements are very accurate from either direction. (Does not apply to FM2000 and FM3000).

- Connect our wide range of flowmeters to any major-brand control system to enjoy superior performance and maximum accuracy.
- Smart value for your equipment budget - up to 2X the working life compared to other brands.
- Work with confidence as a Micro-Trak flowmeter precisely monitors flow of valuable liquids and NH3.
- An ideal choice for liquid application; several stainless-steel models are also NH3 compatible.

FM250 P

1/4" BSP
w/ 1/2" hosebarb
.08-1.6 GPM
290 PSI Max.



FM500

1/2" FPT
.5-5 GPM
500 PSI Max.



FM750 LF GFN

3/4" FPT
.5-12 GPM
150 PSI Max.



FM750 GFN

3/4" FPT
2-40 GPM
150 PSI Max.



FM750 LF SS

3/4" FPT
1-9 GPM
500 PSI Max.



FM750 SS

3/4" FPT
2-40 GPM
500 PSI Max.



FM1000 SS

1" FPT
3.5-70 GPM
500 PSI Max.



FM1500 LF SS

1 1/2" FPT
3.5-70 GPM
500 PSI Max.



FM1500 SS

1 1/2" FPT
10-130 GPM
500 PSI Max.



FM270 LF

2" flange (M200)
.5-15 GPM
225 PSI Max.



FM270

2" flange (M200)
3.5-70 GPM
225 PSI Max.



FM10-100

2" flange (M200)
10-100 GPM
225 PSI Max.



FM2000 P

2" flange (M200)
19-198 GPM
285 PSI Max.



FM3000 P

3" MPT
40-396 GPM
285 PSI Max.



(All pressure ratings @ 70°F)

Micro-Trak Systems Inc.
800-328-9613
Micro-Trak.com
Trakmail@Micro-Trak.com

WHAT SETS US APART:

- Partner/Listen/Customize
- 3-year warranty
- Loaner program

MAGNETIC FLOWMETERS



shown:
MM53
1" FPT
2.6-53 GPM
290 PSI Max.

- No internal moving parts
- Unaffected by fluid viscosity and density
- Highly accurate
- Saves time and money; very low maintenance

MODEL - FLOW RANGE - SIZE:

MM2 - .08 to 1.6 gpm, 3/4" FPT
MM3 - .13 to 2.6 gpm, 3/4" FPT
MM5 - .3 to 5 gpm, 3/4" FPT
MM13 - .6 to 13 gpm, 3/4" FPT
MM26 - 1.3 to 26 gpm, 1" FPT
MM53 - 2.6 to 53 gpm, 1" FPT
MM106 - 5 to 106 gpm, 1 1/2" FPT
MM106FL - 5 to 106 gpm, M220 flange
MM158 - 8 to 158 gpm, 2" MPT
MM238 - 12 to 238 gpm, 2" MPT
(All models max. pressure rated to 290 psi @ 70°F)

SERVO VALVES

Superior quality, fast-acting servo valves — ideally suited for responsive rate changes, and accurate control.

Flanged Servo

12VDC
2" Flange (M200) or
1 1/2" FPT



Threaded Servo

12VDC
1" FPT



9 servo valve models to fit your flow control needs including high-pressure (300 psi) and NH3 ready versions.