

3200 SERIES PUMP PRODUCT TECHNICAL DATA SHEET

OEM: 3214-1E1-52C

AFTERMARKET: 3214-1E1-52C-B (Includes Fittings)

APPLICATION: Agricultural, Chemical and Sprayer application intermittent duty only. This pump is not listed for potable water use.



PUMP DESIGN:

Type: 3 Chamber Positive Displacement Diaphragm
 Maximum Flow: 3.5 GPM [13.25 LPM]
 Fluid Ports: ¾" Quick Attach Female
 Liquid: 140 F [60 C] MAX
 Dry Prime: 10 feet [4.2M]
 Run Dry: Yes
 Shut Off Pressure: 60 PSI [4.1 Bar]
 Control: Pressure Switch

Electrical:

Motor: 110/120 VAC Permanent Magnet, Intermittent Duty
 Voltage Range: 110 VAC – 120 VAC
 Max Amps: 2 Amps
 Protection: Thermal Overload
 Leads: 4' [1.20m] cord with 3 prong plug
 Fuse: 3 Amp recommended
 Control: Pressure Switch
 Max Temp: 180 F [82 C]

Materials of Construction

Housing: Polypropylene
 Valves: Viton
 Diaphragm: Santoprene
 Base: Metal Base
 Hardware: Zinc Plated Steel

AGENCY APPROVALS:

CE, CSA, RoHs, NSF

SHIPPING INFORMATION:

Part Net Weight: 6 lbs [3.62 kg]
 Carton Quantity: 6 Units
 Carton Size: 6" x 22" x 17.75"
 Carton Weight: 38 lbs [17.23 kg]



PSI	GPM	BAR	LPM	Amperage
0	3.50	0.00	13.25	0.50
10	3.25	0.69	12.30	0.60
20	3.00	1.38	11.36	0.75
30	2.75	2.07	10.41	0.80
40	2.50	2.76	9.46	0.95
50	2.00	3.45	7.57	1.05
60	1.75	4.14	6.62	1.25

10425 Wildlife Loop SE, Osakis, MN 56360

Office: 763-253-4740 Fax: 763-253-4741

www.remcoindustries.com

HEAT RISE 3214-1E1-52C

