

Typical Shutoff Valve Assembly

## VALVES

Top quality hand valves for use with spray nozzles, extensions and handles to suit your application needs. Hand valve assemblies may be made from parts shown on this page. The "typical assembly" shown above includes 4727 handle, 4688 valve, 6671-18 curved extension with swivel body, TeeJet cap and flat spray tip.

### AA31

For pressures up to 500 PSI. Comfortable palm fitting gun. For use with any TeeJet spray tip. 1/4" NPS (M) inlet connection.

Forged brass body and nickel-plated steel trigger. PTFE valve seat and packing, stainless steel valve stem. Also supplied as 31-1/4F with 1/4" NPT (F) inlet connection.



### AA36 TRIGGER VALVE WITH TRIGGER LOCK

Choice of 1/4" NPT (F) inlet and outlet, or 3/8" NPT (F) inlet and outlet. Max pressure of 150 PSI. Brass or stainless steel material.



### 6104 TRIGGER VALVE WITH TRIGGER LOCK

Same as 4688 except with 1/4" NPT (F) inlet and outlet connections. Brass material.



### 6466 TRIGGER VALVE

Same as 4688, less trigger lock, with extra long trigger. Brass material.



### 4688 TRIGGER VALVE WITH TRIGGER LOCK

Max flow rate 2 GPM, max pressure of 250 PSI. 1/4" NPT (F) inlet connection, 1/4"-16 (M) outlet connection. Brass material.



### 6590 TRIGGER VALVE

Same as 6104, less trigger lock, with extra long trigger. Brass material.



### 13212 ADAPTER

3/8" NPT (M) outlet, 3/4" garden hose thread inlet for use with 3/8" 36 valve. Brass material.



## VALVE HANDLES

(Choice of valve handles for above valves.)

Outlet connections are 1/4" NPT (M) to fit 1/4" NPT (F) inlets of all valves shown.



### (B)4727 SURE GRIP HANDLE


Brass, rubber-covered, 1/4" NPS (M) inlet connection.



### 4754 SURE GRIP HANDLE

Brass, rubber-covered, 3/4" garden hose thread (F) inlet connection.

## EXTENSIONS



9527



4673

7715

### HIGH-PRESSURE CURVED EXTENSIONS

9527 for pressures to 1,000 PSI. Fits models 23H and 31 GunJet spray guns.

### STRAIGHT & CURVED EXTENSIONS

4673 and 6671 are for pressures to 125 PSI. 7715 is for pressures to 250 PSI. Fits models 23L and 31 GunJet spray guns and trigger valves. CP4743-TEF inlet gasket for use with 4673, 6671, and 7715 extensions.

EXTENSION TYPE & NUMBER	EXTENSION LENGTH (IN.)
9527-8	8
9527-18	18
9527-24	24
9527-36	36
9527-48	48

STRAIGHT WITH FIXED BODY	CURVED WITH SWIVEL BODY	CURVED WITH FIXED BODY	EXTENSION LENGTH (IN.)
7715-8	4673-8	6671-8	8
7715-18	4673-18	6671-18	18
7715-24	4673-24	6671-24	24
7715-30	4673-30	6671-30	30
7715-36	4673-36	6671-36	36
7715-48	4673-48	6671-48	48

### TRIGGERJET® EXTENSION

22665-PP is for use with 22650-PP TriggerJet spray gun. Maximum pressure rating of 150 PSI. Available in 15" and 24" lengths.



22665-PP