

## Typical Applications



FERTILIZER  
DIRECTED  
EXCELLENT

Flow Regulators are usually mounted behind cultivator shanks for the subsurface application of liquid fertilizers and soil fumigants. They are also used for above-ground streaming applications.



**CP1322**  
1/4TT Body



**5053**  
Strainer



**CP4916**  
Orifice Plate



**CP4928**  
Adapter 1/8" NPT (F)  
Outlet



**CP1325**  
Cap



**Note:** Always insert orifice plate with side marked with number facing the outlet.  
MATERIAL: Stainless Steel

### TIP STRAINER MESH RECOMMENDATION

FOR ORIFICE SIZE	USE MESH SIZE
15 and Smaller	200
16-39	100
40-70	50
72 and Larger	—

To determine the orifice plates you need, use the following equations:

$$\text{GPM (Per Nozzle)} = \frac{\text{GPA} \times \text{MPH} \times W}{5,940}$$

$$GPM = \frac{5,940 \times \text{GPM (Per Nozzle)}}{\text{MPH} \times W}$$

Tabulated flow rates are for spraying water into air at atmospheric pressure. If your application creates backpressure, or if spraying into a liquid, measure and calibrate to ensure proper application rates. For spraying solutions other than water, see page 185 for conversion factors.

- W = Nozzle spacing (in inches) for broadcast spraying.
- = Spray width (in inches) for single nozzle, band spraying or boomless spraying.
- = Row spacing (in inches) divided by the number of nozzles per row for directed spraying.

ORIFICE PLATE PART NO.	CAPACITY (GPM)						
	5 PSI	10 PSI	20 PSI	30 PSI	40 PSI	50 PSI	60 PSI
<b>CP4916-008</b>	0.003	0.004	0.006	0.007	0.008	0.009	0.010
<b>CP4916-10</b>	0.005	0.007	0.009	0.011	0.013	0.015	0.016
<b>CP4916-12</b>	0.007	0.010	0.013	0.016	0.019	0.021	0.023
<b>CP4916-14</b>	0.009	0.013	0.018	0.022	0.025	0.028	0.031
<b>CP4916-15</b>	0.010	0.015	0.021	0.025	0.029	0.032	0.036
<b>CP4916-16</b>	0.012	0.017	0.023	0.029	0.033	0.037	0.040
<b>CP4916-18</b>	0.015	0.021	0.030	0.036	0.042	0.047	0.051
<b>CP4916-20</b>	0.018	0.026	0.037	0.045	0.052	0.058	0.064
<b>CP4916-22</b>	0.022	0.031	0.043	0.053	0.061	0.068	0.075
<b>CP4916-24</b>	0.026	0.037	0.052	0.064	0.074	0.083	0.091
<b>CP4916-25</b>	0.028	0.040	0.056	0.068	0.079	0.088	0.097
<b>CP4916-26</b>	0.030	0.043	0.061	0.074	0.086	0.096	0.105
<b>CP4916-27</b>	0.032	0.046	0.064	0.079	0.091	0.102	0.111
<b>CP4916-28</b>	0.035	0.049	0.069	0.085	0.098	0.110	0.120
<b>CP4916-29</b>	0.038	0.054	0.076	0.094	0.108	0.121	0.132
<b>CP4916-30</b>	0.040	0.057	0.081	0.099	0.114	0.127	0.140
<b>CP4916-31</b>	0.043	0.062	0.087	0.107	0.123	0.138	0.151
<b>CP4916-32</b>	0.048	0.068	0.095	0.117	0.135	0.151	0.165
<b>CP4916-34</b>	0.052	0.074	0.104	0.127	0.147	0.164	0.180
<b>CP4916-35</b>	0.056	0.079	0.111	0.136	0.157	0.176	0.192
<b>CP4916-37</b>	0.061	0.086	0.122	0.149	0.172	0.192	0.211
<b>CP4916-39</b>	0.068	0.096	0.135	0.165	0.191	0.214	0.234
<b>CP4916-40</b>	0.072	0.102	0.144	0.177	0.204	0.228	0.250
<b>CP4916-41</b>	0.075	0.106	0.149	0.183	0.211	0.236	0.258
<b>CP4916-43</b>	0.082	0.116	0.163	0.200	0.231	0.258	0.283
<b>CP4916-45</b>	0.088	0.125	0.177	0.217	0.250	0.280	0.306
<b>CP4916-46</b>	0.095	0.135	0.191	0.234	0.270	0.302	0.331

**Note:** Always double check your application rates. Tabulations are based on spraying water at 70°F. See technical information (pages 179-202) for useful formulas and other technical information.

# TeeJet® FLOW REGULATORS

ORIFICE PLATE PART NO.	CAPACITY (GPM)						
	5 PSI	10 PSI	20 PSI	30 PSI	40 PSI	50 PSI	60 PSI
CP4916-47	0.097	0.138	0.194	0.238	0.275	0.307	0.337
CP4916-48	0.101	0.143	0.202	0.248	0.286	0.320	0.350
CP4916-49	0.104	0.148	0.209	0.255	0.295	0.330	0.361
CP4916-51	0.116	0.165	0.233	0.285	0.329	0.368	0.403
CP4916-52	0.118	0.168	0.237	0.290	0.335	0.375	0.410
CP4916-54	0.127	0.180	0.255	0.312	0.360	0.402	0.441
CP4916-55	0.133	0.189	0.267	0.326	0.377	0.421	0.462
CP4916-57	0.141	0.200	0.283	0.346	0.400	0.447	0.490
CP4916-59	0.153	0.217	0.306	0.375	0.433	0.484	0.530
CP4916-61	0.165	0.233	0.330	0.404	0.466	0.521	0.571
CP4916-63	0.174	0.246	0.347	0.425	0.491	0.549	0.601
CP4916-65	0.185	0.261	0.369	0.452	0.522	0.584	0.639
CP4916-67	0.196	0.278	0.392	0.481	0.555	0.621	0.680
CP4916-68	0.203	0.287	0.405	0.496	0.573	0.641	0.702
CP4916-70	0.216	0.306	0.433	0.530	0.612	0.684	0.750
CP4916-72	0.226	0.320	0.453	0.554	0.640	0.716	0.784
CP4916-73	0.233	0.330	0.467	0.572	0.660	0.738	0.808
CP4916-75	0.245	0.347	0.491	0.601	0.694	0.776	0.850
CP4916-78	0.272	0.385	0.544	0.667	0.770	0.861	0.943
CP4916-80	0.280	0.397	0.561	0.687	0.793	0.887	0.971
CP4916-81	0.290	0.411	0.581	0.711	0.821	0.918	1.01
CP4916-83	0.317	0.449	0.634	0.777	0.897	1.00	1.10
CP4916-86	0.332	0.470	0.664	0.813	0.939	1.05	1.15
CP4916-89	0.346	0.490	0.693	0.849	0.980	1.10	1.20
CP4916-91	0.369	0.523	0.739	0.905	1.05	1.17	1.28
CP4916-93	0.387	0.547	0.774	0.947	1.09	1.22	1.34
CP4916-95	0.404	0.572	0.808	0.990	1.14	1.28	1.40

**Note:** Always double check your application rates. Tabulations are based on spraying water at 70°F. See technical information (pages 179–202) for useful formulas and other technical information.

## HOW TO ORDER

C P 4 9 1 6 - 0 0 8

Orifice Plate

Capacity Size

ORIFICE PLATE PART NO.	CAPACITY (GPM)						
	5 PSI	10 PSI	20 PSI	30 PSI	40 PSI	50 PSI	60 PSI
CP4916-98	0.442	0.625	0.884	1.08	1.25	1.40	1.53
CP4916-103	0.461	0.653	0.923	1.13	1.31	1.46	1.60
CP4916-107	0.518	0.733	1.04	1.27	1.47	1.64	1.79
CP4916-110	0.548	0.775	1.10	1.34	1.55	1.73	1.90
CP4916-115	0.605	0.855	1.21	1.48	1.71	1.91	2.09
CP4916-120	0.629	0.890	1.26	1.54	1.78	1.99	2.18
CP4916-125	0.693	0.980	1.39	1.70	1.96	2.19	2.40
CP4916-128	0.721	1.02	1.44	1.77	2.04	2.28	2.50
CP4916-132	0.774	1.10	1.55	1.90	2.19	2.45	2.68
CP4916-136	0.840	1.19	1.68	2.06	2.38	2.66	2.91
CP4916-140	0.894	1.27	1.79	2.19	2.53	2.83	3.10
CP4916-144	0.926	1.31	1.85	2.27	2.62	2.93	3.21
CP4916-147	0.953	1.35	1.91	2.33	2.70	3.01	3.30
CP4916-151	1.04	1.47	2.08	2.55	2.94	3.29	3.60
CP4916-156	1.10	1.55	2.20	2.69	3.11	3.47	3.80
CP4916-161	1.15	1.63	2.31	2.83	3.27	3.65	4.00
CP4916-166	1.21	1.72	2.43	2.97	3.43	3.84	4.20
CP4916-170	1.30	1.84	2.61	3.19	3.69	4.12	4.51
CP4916-172	1.36	1.92	2.71	3.32	3.84	4.29	4.70
CP4916-177	1.41	2.00	2.83	3.46	4.00	4.47	4.90
CP4916-182	1.47	2.08	2.95	3.61	4.17	4.66	5.10
CP4916-187	1.56	2.21	3.12	3.82	4.41	4.93	5.40
CP4916-196	1.73	2.45	3.46	4.24	4.90	5.47	6.00
CP4916-205	1.88	2.65	3.75	4.59	5.31	5.93	6.50
CP4916-218	2.11	2.98	4.21	5.16	5.96	6.66	7.30
CP4916-234	2.45	3.47	4.91	6.01	6.94	7.76	8.50
CP4916-250	2.83	4.00	5.66	6.93	8.00	8.94	9.80

