COMBO-JET_® Caps, Adapters & Strainers

Wilger manufacturers a variety of caps that are used for metering flow rates (through hose barb, push-in tube, or streamer caps) or used as accessories for other spraying or plumbing functions.

Plug Caps



40272-B5

Caps unused Combo-Jet nozzle body outlets

Plug Cap		
Assembled Plug	Cap Only	
40272-B5	40272-05	
40272-B5	40272-05	

Hose Barb Caps



40260-00

40261-00

Stainless

Steel for

Chemical

Spraying

40250-00

Mesh Size

100 mesh

25 mesh

Hose barb caps can be used as manifold plumbing parts or for metering flow.

Hose Barb Caps			
Barb Size	ize FKM O-ring Assy Cap Only		
1/8"	40420-B5	40420-05	
1/4"	40422-B5	40422-05	
3/8"	40424-B5	40424-05	
1/2"	40426-B5	40426-05	

To use cap for metering, order CAP ONLY, with o-ring and 40285-## metering orifice.

COMBO-JET Cap 0-rings

13mm x 3mm o-ring

for COMBO-JET®

Caps & Spray Tips

COMBO-JET Snap-in Strainers Combo-jet strainers snap into a metering orifice or cap for an assembly that handles as 'one-piece'

40251-00 40249-00

40249-00

40248-00

Slotted Strainer | Stainless Mesh

use 100 mesh for -02 nozzles o

Adapter for non-metering caps Seal adapter is used to keep o-ring in place if metering orifice

is NOT used

Slotted

Plastic

Strainer

for

#40251-00

#40250-00 use 50 mesh for -025 or larger nozzles

Push-in-Tube Caps



Quick connect tube caps seal on the outside diameter of a tube, and used as manifold plumbing parts or for metering flow.

Quick Connect/Push-in-tube Caps			
Tube Size (O.D.)	FKM O-ring Assy	Cap Only	
1/4"	40435-B5	40435-05	
5/16"	40437-B5	40437-05	
3/8"	40436-B5	40436-05	

To use cap for metering, order CAP ONLY, with o-ring and 40285-## metering orifice.

Threaded Outlet Adapters



Combo-Jet Cap with NPT-F threaded port

Threaded Outlet Caps			
Thread Size	FKM O-ring Assy	Cap Only	
1/8" NPT-F	40277-B5	40277-05	
1/4" NPT-F	40273-B5	40273-05	
45° 1/4" NPT-F	40274-B5	40274-05	

For applications that do not required liquid metering orifices (e.g. plumbing manifolds), the -B5 is an assembly that includes an o-ring (#40260-00), seal adapter (#40261-00 in lieu of orifice), and cap.

Hose Drop & Extension Caps

Hose Drop Caps are used to feed or spray down below a canopy to minimize crop contact.

Outlet	Length	Part #	
Combo-Jet	2"	40210-00	
to Combo-Jet	5"	40211-00	
Combo-Jet Cap to 1/4" NPT-M	16"	22026-00	
	24"	22036-00	
	36"	22038-00	
1/4 INF 1-IVI	48"	22048-00	
	2.25"	5.25	



Other styles of Hose Drop Assemblies using threaded inlets are also available. Find them in the DRY BOOMS section of the catalog.

Fertilizer Streamer Caps



3-hole Fertilizer Streamer Caps [Molded]

3-hole fertilizer streamer (FS3) nozzle improves stream consistency across higher pressure ranges



Color-coded, Single part number ordering

VISIT PAGE 28-29 for both FS3 Fertilizer Streamer Caps & metering orifice charts

2-hole Streamer Caps [Drilled]





3-hole Streamer Caps [Drilled]

3-hole streamer caps are used to stream liquid fertilizer





Drilled Fertilizer Streamer Caps [CAP ONLY]			
Cap Size	Flow Range	2-Hole Cap	3-Hole Cap
Small	0.05 - 0.4 us gpm	40432-047	40433-047
Medium	0.2 - 1.0 us gpm	40432-086	40433-067
Large	0.5 - 3.0 us gpm	40432-104	40433-104
Large	0.5 - 3.0 us gpm	40432-104	40433-104

Ordering [Drilled] Streamer Caps

For drilled streamer cap assembly, order:

- 1. Metering Orifice (40285-## series)*
- 2. Streamer cap (2 or 3 hole, sized to flow range
- 3. O-ring seal (40260-00 or 40260-V0)
- 4. [Optional] Slotted Strainer

*For selecting metering orifices to fit your application, use Tip Wizard, consult flow charts, or use other tools available at www.wilger.net



Square Lug Nozzle Outlet Caps - Only for Square Lug Nozzle Body Outlets (Teejet, Hypro, etc)



40197-05 Square Lug nozzle outlet plug cap

3/8" Slot Cap

40248-00

Color

Blue

40260-V0



40159-05 For 3/8" wide flanged spray tips

Threaded Cap



45° 1/4" NPT-F thread

Flanged Strainers



Stainless Steel Strainers for Square-Lug Caps & Nozzles

Cap Gaskets



Gaskets are required to seal all Square Lug Caps