

Made with high quality investment cast 316 stainless steel components, the ChemFlo® series of pumps are designed to be applied in a wide range of pumping applications where stainless steel is required.

The ChemFlo® 2 pumps utilize a semi open impeller design to allow for passage of larger solid sizes than similar sized enclosed impellers. Several mechanical seal options are available in addition to the standard type 2100 carbon / ceramic / Viton mechanical seal.

ChemFlo® 2 pumps are offered in two configurations, pump (with motor) and PumPAK® (without motor) versions. Electric and hydraulic motors can be close coupled to ChemFlo® 2 pumps or pedestal mounted versions are also available for long coupling.

Further expanding the versatility of the ChemFlo® series is the CFB 2 pump, a ChemFlo® 2 in NiBrAl material. All wetted parts are produced in CA 958 nickel aluminum bronze including the drive sleeve to maximize corrosion protection in seawater applications.

If ordering a pumpak with a 145TC please note that the electric motor must have a base.



Application

- Agricultural
- Commercial
- Industrial
- Marine
- OEM

Drive Sleeve

• 316 stainless steel

SPECIFICATIONS:

Suction And Discharge 1-1/2" x 1" NPT

Materials Of Construction 316 stainless steel, CFB (nickel aluminum

bronze)

Flow Up to 108 GPM

Head Feet Up to 103'

Impeller 5.25" semi-open, cast 316 stainless steel

Motor Up to 3 HP

Drive Options Close coupled 56C, Close coupled 145TC,

Pedestal, PumPAK® (without motor)

Seal Special seal material combinations

available (consult factory), Standard


carbon / ceramic / Viton

Options Hydraulic motor .22 cu. in., Hydraulic


motor .37 cu. in., Tap for recirculation or


seal flush


CHEMFLO 2




CHEMFLO 2








CHEMFLO 2



30478




	ITEM NO.	PART NO.	DESCRIPTION	QTY.
	1	21255	PIPE PLUG S.S 1/8 NPT	1
	2	29906	HOUSING S.S.	1
	3	29912	IMPELLER S.S 5.25 DIA.	1
	4	29785	DRIVE SLEEVE S.S.	1
	5	21238	LOCKWASHER S.S 5/16	4
	6	21242	HEX HD. CAPSCREW S.S 5/16-18 X .88	4
	7	35598	HEX JAM NUT S.S.	1
*	8	29715	O RING - VITON	1
*	9	30061	SEAL ASSY 3/4" T-2100	1
	10	25663	HEX. HD. CAPSCREW S.S 3/8-16 X 3.4	4
	11	21266	LOCKWASHER S.S 3/8	4
	12	29908	ADAPTER S.S.	1
	13	28049	CLAMP S.S 3/4" SL.	1
	14	29670	PEDESTAL ASSY.	1

^{*-} RECOMMENDED REPLACEMENT PARTS



29916




ITE	M NO.	PART NO.	DESCRIPTION	QTY.
<i>'</i>	1	21255	PIPE PLUG S.S 1/8 NPT	1
	2	29906	HOUSING S.S.	1
	3	29912	IMPELLER S.S 5.25 DIA.	1
	4	29785	DRIVE SLEEVE S.S.	1
	5	21238	LOCKWASHER S.S 5/16	4
	6	21242	HEX HD. CAPSCREW S.S 5/16-18 X .88	4
	7	35598	HEX JAM NUT S.S.	1
*	8	29715	O RING - VITON	1
*	9	30061	SEAL ASSY 3/4" T-2100	1
	10	29908	ADAPTER S.S.	1
	11	28049	CLAMP S.S 3/4" SL.	1



^{*-} RECOMMENDED REPLACEMENT PARTS

36381



	ITEM NO.	PART NO.	DESCRIPTION	QTY.
•	1	36355	PIPE PLUG BRONZE - 1/8 NPT	1
	2	36341	HOUSING BRONZE	1
	3	36354	HEX JAM NUT BRONZE - 3/8-24	1
	4	36349	IMPELLER BRONZE - 5.25 DIA.	1
*	5	29715	O RING - VITON	1
	6	36353	DRIVE SLEEVE BRONZE	1
*	7	30061	SEAL ASSY 3/4" T-2100	1
	8	25663	HEX HD. CAPSCREW S.S 3/8-16 X .75	4
	9	21266	LOCKWASHER S.S 3/8	4
	10	21238	LOCKWASHER S.S 5/16	4
	11	21242	HEX HD. CAPSCREW S.S 5/16-18 X .88	4
	12	36384	CLAMP S.S 3/4" SL.	1
	13	36345	ADAPTER BRONZE	1

^{*-} RECOMMENDED REPLACEMENT PARTS

